



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
08/987,775	12/09/1997	ACHIM GREFENSTEIN	47587/48070	6702
26474 7590 11/24/2008 NOVAK DRUCE DELUCA + QUIGG LLP 1300 EYE STREET NW SUITE 1000 WEST TOWER WASHINGTON, DC 20005				
EXAMINER				
KRUER, KEVIN R				
ART UNIT		PAPER NUMBER		
1794				
MAIL DATE		DELIVERY MODE		
11/24/2008		PAPER		

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary

Application No.

08/987,775

Applicant(s)

GREFENSTEIN ET AL.

Examiner

KEVIN R. KRUEER

Art Unit

1794

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --
Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 23 September 2008.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 24, 26, 30, 31, 34, 41 and 43 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 24, 26, 30, 31, 34, 41 and 43 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☐ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☐ Information Disclosure Statement(s) (PTO-144a or PTO-836a)
Paper No(s)/Mail Date _____
- 4) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date _____
- 5) ☐ Notice of Intervenor Patent Application (PTO-152)
- 6) ☐ Other: _____

DETAILED ACTION

Claim Rejections - 35 USC § 103

1. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.
2. Claims 24, 31, and 41 are rejected under 35 U.S.C. 103(a) as being unpatentable over Fischer et al. (US 5,747,568) in view of (a) WO96/09928 (aka Sallmetall), (b) Rosenau et al. (US 5,821,302) and (c) Nishihara (US 5,900,446) or Margotte et al (US 4,204,047).

Fischer teaches a molding material comprising 30-80wt% of an elastomeric grafting base and 20-70wt% of a shell grafted onto the grafting base (abstract). The grafting base comprises 90-99.9% of at least one alkyl acrylate and 0.1-10wt% of a polyfunctional crosslinking monomer. The shell comprises 0-100% styrene or substituted styrenes, and 0-100% of an acrylonitrile or methyl methacrylate. The above-described particles are dispersed in a hard matrix comprising 60-90wt% styrene or substituted styrene and 10-40% acrylonitrile (col 1, lines 48-col2, line 16). The composition may further contain up to 30t% of additives such as fibers (Col 4, lines 26-34). This composition exhibit good weather resistance, aging resistance, and high impact strength (col 4, lines 46-53), and are usable as signs (col 4, line 48).

Fischer does not teach that the molding material may be overlaid with a PMMA transparent layer and a transparent protective film. However, Sallmetall teaches a light transmitting cover foil intended for adhesion to an information-carrying surface (page 1, lines 1-5). The first layer of the cover foil comprises a deformable plastic (abstract). The

examiner interprets the taught deformable plastic layer to read on the claimed transparent protective film of claim 41 because it will inherently provide the film with some layer of protection. The deformable plastic layer may be textured or patterned if desired (page 1, lines 30+). The cover foil further comprises a dimensionally stable carrier layer comprising, for instance, PMMA (abstract). The examiner notes that the taught dimensionally stable carrier layer reads on Applicant's claimed "transparent top layer of PMMA." A thermally activated hot melt layer comprising EVA, EEA, EBA, EMA, GBA or other low melting thermoplastics may be utilized to adhere the deformable plastic to the carrier sheet (abstract). The layers may be mutually connected via coextrusion (page 2, lines 14-16). It would have been obvious to one of ordinary skill in the art to utilize the cover film taught in Sallmetall on the sign taught in Fischer in order to protect the sign and provide the sign with the desired texturing and patterning.

Fischer also does not teach that the composition may comprise a polycarbonate. However, Margotte and Nishihara each individually teaches a composition comprising a core/shell graft copolymer compounded with polycarbonate. Margotte teaches the addition of 20-80pbw polycarbonate to said mixture (abstract). The polycarbonate should have a molecular weight of 20,000-80,000 (col 4, lines 1+) and is granulated (col 6, lines 1+). Said mixture has the benefit of improved strength, dimensional stability, and processability (col 2, lines 1+). Nishihara teaches a composition comprising a core/shell polymer and 10-90pbw of polycarbonate (col 4, lines 30+) with a molecular weight of 10,000-100,000 (col 6, line 56). Said blend has a good combination of processability, impact resistance and rigidity (col 7, lines 45+). Thus, it would have

Art Unit: 1794

been obvious to one of ordinary skill in the art at the time the invention was made to compound the core/shell graft copolymer taught in Fischer with 10-90pbw polycarbonate. The motivation for doing so would have been to improve the composition's processability, high impact resistance, and rigidity.

With respect to the "ground or granulated" limitation, the examiner takes the position said limitation is a method limitation. Specifically, the specification teaches that the polycarbonate is added in "granulated or ground" form (page 18-page 19) and then mixed with the other components at 180-400°C (page 21, lines 26+). At those processing temperatures, the polycarbonate will melt and will not maintain its granulated or ground form (polycarbonate is herein understood to typically melt at 374-500°F). Thus, the method in which the polycarbonate is supplied to the composition is herein understood not to materially affect the final product. No showing has been made that the form in which the polycarbonate is supplied affects the final product.

Fischer does not teach the claimed particle size of the graft copolymer. However, Rosenau teaches the particle size of said particles may be selected based upon the desired glossiness/roughness of the resulting layer (col 3, lines 5+). Thus, it would have been obvious to the skilled artisan to optimize the particle size of the graft polymers taught in Fischer in order to optimize the desired gloss/dullness of the resulting film.

3. Claims 24, 31, 34, and 41 are rejected under 35 U.S.C. 103(a) as being unpatentable over Fischer et al. (US 5,747,568) in view of (a) Ellison US 5,985,079), (b)

Rosenau et al. (US 5,821,302) and (c) Nishihara (US 5,900,446) or Margotte et al (US 4,204,047).

Fischer teaches a molding material comprising 30-80wt% of an elastomeric grafting base and 20-70wt% of a shell grafted onto the grafting base (abstract). The grafting base comprises 90-99.9% of at least one alkyl acrylate and 0.1-10wt% of a polyfunctional crosslinking monomer. The shell comprises 0-100% styrene or substituted styrenes, and 0-100% of an acrylonitrile or methyl methacrylate. The above-described particles are dispersed in a hard matrix comprising 60-90wt% styrene or substituted styrene and 10-40% acrylonitrile (col 1, lines 48-col2, line 16). The composition may further contain up to 30t% of additives such as fibers (Col 4, lines 26-34). This composition exhibit good weather resistance, aging resistance, and high impact strength (col 4, lines 46-53), and are usable as automobile parts (col 4, line 48).

Fischer does not teach the application of transparent surface coatings to the taught composition. However, Ellison teaches a flexible composite surfacing film for providing a substrate with desired surface characteristics. The film comprises a flexible transparent outer polymer clear coat layer and a pigmented base coat layer is adhered to said outer clear coat layer and is visible there through (abstract). The transparent outer polymer clear coat layer may comprise outer and inner layers of differing properties. For example, both layers may comprise a blend of fluorinated polymer and an acrylic resin. However, the outer layer may be rich in the fluorinated polymer to enhance weatherability, and the inner layer may be rich in acrylic resin to improve bonding to the pigmented layer (col 7, lines 15-37). The acrylic resin may be polymethyl

Art Unit: 1794

methacrylate homopolymers (col 6, lines 24-42). Both polymers may be extruded from the same extrusion die (col 7, line 40). The pigmented polymer may also be extruded (col 8, line 35). The surfacing film may be applied to polymeric supporting substrates in accordance with known laminating or bonding techniques. Particularly suitable shaped articles of the invention are exterior automobile parts (col 11, line 36). Thus, it would have been obvious to one of ordinary skill in the art to apply the surfacing film taught in Ellison to the composition taught in Fischer in order to supply the composition with the desired surface characteristics.

Fischer also does not teach that the composition may comprise a polycarbonate. However, Margotte and Nishihara each individually teaches a composition comprising a core/shell graft copolymer compounded with polycarbonate. Margotte teaches the addition of 20-80pbw polycarbonate to said mixture (abstract). The polycarbonate should have a molecular weight of 20,000-80,000 (col 4, lines 1+) and is granulated (col 6, lines 1+). Said mixture has the benefit of improved strength, dimensional stability, and processability (col 2, lines 1+). Nishihara teaches a composition comprising a core/shell polymer and 10-90pbw of polycarbonate (col 4, lines 30+) with a molecular weight of 10,000-100,000 (col 6, line 56). Said blend has a good combination of processability, impact resistance and rigidity (col 7, lines 45+). Thus, it would have been obvious to one of ordinary skill in the art at the time the invention was made to compound the core/shell graft copolymer taught in Fischer with 10-90pbw polycarbonate. The motivation for doing so would have been to improve the composition's processability, high impact resistance, and rigidity.

With respect to the "ground or granulated" limitation, the examiner takes the position said limitation is a method limitation. Specifically, the specification teaches that the polycarbonate is added in "granulated or ground" form (page 18-page 19) and then mixed with the other components at 180-400°C (page 21, lines 26+). At those processing temperatures, the polycarbonate will melt and will not maintain its granulated or ground form (polycarbonate is herein understood to typically melt at 374-500°F). Thus, the method in which the polycarbonate is supplied to the composition is herein understood not to materially affect the final product. No showing has been made that the form in which the polycarbonate is supplied affects the final product.

Fischer does not teach the claimed particle size of the graft copolymer. However, Rosenau teaches the particle size of said particles may be selected based upon the desired glossiness/roughness of the resulting layer (col 3, lines 5+). Thus, it would have been obvious to the skilled artisan to optimize the particle size of the graft polymers taught in Fischer in order to optimize the desired gloss/dullness of the resulting film.

4. Claims 24, 31, and 41 are rejected under 35 U.S.C. 103(a) as being unpatentable over Rosenau et al. (US 5,821,302) in view of (a) Ellison (US 5,985,079) and (b) Margotte et al (US 4,204,047).

Rosenau teaches a thermoplastic molding composition comprising (a) 50-100wt% of a styrene compound, and (b) 0.1-70wt% of a graft polymer. The styrene compound may comprise 0-40wt% acrylonitrile. The graft polymer comprises 30-90wt% of a core, and 10-70wt% of a graft shell. The core comprises 50-99.99wt% of C1-10

Art Unit: 1794

alkyl acrylate, and 0.01-5wt% of a polyfunctional crosslinking monomer. The shell comprises 50-100wt% styrene and 0-40wt% acrylonitrile (col 1, lines 4-65). The graft polymer has an average particle diameter of less than 700nm. The composition may further comprise up to 70wt% of a particulate polymer and up to 70wt% of a polycarbonate blend (col 9, lines 59+). The composition is useful in extrusions, injection moldings, calendaring, and rolling (col 10, lines 58-64).

Rosenau teaches the composition may comprise polycarbonate but does not teach the claimed molecular weight of said polycarbonate. However, Margotte teaches a composition comprising an impact resistance of a core/shell graft copolymer compounded with polycarbonate. Margotte teaches the addition of 20-80pbw polycarbonate to said mixture (abstract). The polycarbonate should have a molecular weight of 20,000-80,000 (col 4, lines 1+) and is granulated (col 6, lines 1+). Said mixture has the benefit of improved strength, dimensional stability, and processability (col 2, lines 1+). Thus, it would have been obvious to one of ordinary skill in the art at the time the invention was made to compound the core/shell graft copolymer taught in Rosenau with polycarbonate having a molecular weight of 20,000-80,000. The motivation for doing so would have been to improve the composition's processability, high impact resistance, and rigidity.

Rosenau does not teach the claimed top coat or protective coat may be applied to the taught composition. However, Ellison teaches a flexible composite surfacing film for providing a substrate with desired surface characteristics. The film comprises a flexible transparent outer polymer clear coat layer and a pigmented base coat layer is

Art Unit: 1794

adhered to said outer clear coat layer and is visible there through (abstract). The transparent outer polymer clear coat layer may comprise outer and inner layers of differing properties. For example, both layers may comprise a blend of fluorinated polymer and an acrylic resin. However, the outer layer may be rich in the fluorinated polymer to enhance weatherability, and the inner layer may be rich in acrylic resin to improve bonding to the pigmented layer (col 7, lines 15-37). The acrylic resin may be polymethyl methacrylate homopolymers (col 6, lines 24-42). Both polymers may be extruded from the same extrusion die (col 7, line 40). The pigmented polymer may also be extruded (col 8, line 35). The surfacing film may be applied to polymeric supporting substrates in accordance with known laminating or bonding techniques. Particularly suitable shaped articles of the invention are exterior automobile parts (col 11, line 36). Thus, it would have been obvious to one of ordinary skill in the art to apply the surfacing film taught in Ellison to the composition taught in Rosenau in order to supply the composition with the desired surface characteristics.

With respect to the "ground or granulated" limitation, the examiner takes the position said limitation is a method limitation. Specifically, the specification teaches that the polycarbonate is added in "granulated or ground" form (page 18-page 19) and then mixed with the other components at 180-400°C (page 21, lines 26+). At those processing temperatures, the polycarbonate will melt and will not maintain its granulated or ground form (polycarbonate is herein understood to typically melt at 374-500°F). Thus, the method in which the polycarbonate is supplied to the composition is herein

Art Unit: 1794

understood not to materially affect the final product. No showing has been made that the form in which the polycarbonate is supplied affects the final product.

5. Claims 24 and 31 are rejected under 35 U.S.C. 103(a) as being unpatentable over Rosenau et al. (US 5,821,302) in view of (a) Trabert et al. (US 5,318,737) and (b) Margotte et al (US 4,204,047).

Rosenau teaches a thermoplastic molding composition comprising (a) 50-100wt% of a styrene compound, and (b) 0.1-70wt% of a graft polymer. The styrene compound may comprise 0-40wt% acrylonitrile. The graft polymer comprises 30-90wt% of a core, and 10-70wt% of a graft shell. The core comprises 50-99.99wt% of C1-10 alkyl acrylate, and 0.01-5wt% of a polyfunctional crosslinking monomer. The shell comprises 50-100wt% styrene and 0-40wt% acrylonitrile (col 1, lines 4-65). The graft polymer has an average particle diameter of less than 700nm. The composition may further comprise up to 70wt% of a particulate polymer and up to 70wt% of a polycarbonate component (col 9, lines 59+). The composition is useful in extrusions, injection moldings, calendaring, and rolling (col 10, lines 58-64), and may be utilized to make automotive parts.

Rosenau does not teach that a transparent PMMA coating should be applied over the taught composition. However, Trabert teaches a capstock composition comprising an acrylic polymer and an acrylic based impact-modifying agent (abstract). The acrylic resin may comprise polymerized methyl methacrylate (col 6, line 16). The composition has particularly good flexural modulus and impact strength (col 5, line 27), scratch resistance, thermal resistance, and chemical resistance. Such resin

Art Unit: 1794

compositions can be extruded onto the desired substrate (col 5, lines 29+) or coextruded with the substrate (col 5, lines 48+). The capstocks are especially useful with structural plastics (col 9, lines 1+). It would have been obvious to one of ordinary skill in the art to coextrude the capstock taught in Trabert with the composition taught in Rosenau in order to improve its chemical resistance, and impact strength.

Rosenau teaches the composition may comprise polycarbonate but does not teach the claimed molecular weight of said polycarbonate. However, Margotte teaches a composition comprising an impact resistance of a core/shell graft copolymer compounded with polycarbonate. Margotte teaches the addition of 20-80pbw polycarbonate to said mixture (abstract). The polycarbonate should have a molecular weight of 20,000-80,000 (col 4, lines 1+) and is granulated (col 6, lines 1+). Said mixture has the benefit of improved strength, dimensional stability, and processability (col 2, lines 1+). Thus, it would have been obvious to one of ordinary skill in the art at the time the invention was made to compound the core/shell graft copolymer taught in Rosenau with polycarbonate having a molecular weight of 20,000-80,000. The motivation for doing so would have been to improve the composition's processability, high impact resistance, and rigidity.

With respect to the "ground or granulated" limitation, the examiner takes the position said limitation is a method limitation. Specifically, the specification teaches that the polycarbonate is added in "granulated or ground" form (page 18-page 19) and then mixed with the other components at 180-400°C (page 21, lines 26+). At those processing temperatures, the polycarbonate will melt and will not maintain its granulated

or ground form (polycarbonate is herein understood to typically melt at 374-500°F).

Thus, the method in which the polycarbonate is supplied to the composition is herein understood not to materially affect the final product. No showing has been made that the form in which the polycarbonate is supplied affects the final product.

6. Claims 24, 31, and 41 are rejected under 35 U.S.C. 103(a) as being unpatentable over Rosenau et al. (US 5,821,302) in view of (a) EP006421 (aka Endoh) and (b) Margotte et al (US 4,204,047).

Rosenau teaches a thermoplastic molding composition comprising (a) 50-100wt% of a styrene compound, and (b) 0.1-70wt% of a graft polymer. The styrene compound may comprise 0-40wt% acrylonitrile. The graft polymer comprises 30-90wt% of a core, and 10-70wt% of a graft shell. The core comprises 50-99.99wt% of C1-10 alkyl acrylate, and 0.01-5wt% of a polyfunctional crosslinking monomer. The shell comprises 50-100wt% styrene and 0-40wt% acrylonitrile (col 1, lines 4-65). The graft polymer has an average particle diameter of less than 700nm. The composition may further comprise up to 70wt% of a particulate polymer and up to 70wt% of a polycarbonate blend (col 9, lines 59+). The composition is useful in extrusions, injection moldings, calendaring, and rolling (col 10, lines 58-64).

Rosenau does not teach that a PMMA transparent layer or a protective topcoat may be applied to the taught composition. However, Endoh teaches an extrusion laminate comprising a polyvinylidene fluoride layer, and an adhesive layer comprising a methyl methacrylate polymer (abstract). The methyl methacrylate polymer may

comprise PMMA (page 9, lines 14+). The polyvinylidene fluoride layer provides the laminate with excellent weather resistance and chemical resistance. Thus, it would have been obvious to one of ordinary skill in the art to extrude the composition taught in Rosenau with the polyvinylidene fluoride and PMMA layers taught in Endoh in order to improve the composition's weather and chemical resistance.

Rosenau teaches the composition may comprise polycarbonate but does not teach the claimed molecular weight of said polycarbonate. However, Margotte teaches a composition comprising an impact resistance of a core/shell graft copolymer compounded with polycarbonate. Margotte teaches the addition of 20-80pbw polycarbonate to said mixture (abstract). The polycarbonate should have a molecular weight of 20,000-80,000 (col 4, lines 1+) and is granulated (col 6, lines 1+). Said mixture has the benefit of improved strength, dimensional stability, and processability (col 2, lines 1+). Thus, it would have been obvious to one of ordinary skill in the art at the time the invention was made to compound the core/shell graft copolymer taught in Rosenau with polycarbonate having a molecular weight of 20,000-80,000. The motivation for doing so would have been to improve the composition's processability, high impact resistance, and rigidity.

With respect to the "ground or granulated" limitation, the examiner takes the position said limitation is a method limitation. Specifically, the specification teaches that the polycarbonate is added in "granulated or ground" form (page 18-page 19) and then mixed with the other components at 180-400°C (page 21, lines 26+). At those processing temperatures, the polycarbonate will melt and will not maintain its granulated

Art Unit: 1794

or ground form (polycarbonate is herein understood to typically melt at 374-500°F).

Thus, the method in which the polycarbonate is supplied to the composition is herein understood not to materially affect the final product. No showing has been made that the form in which the polycarbonate is supplied affects the final product.

7. Claims 24, 31, and 41 are rejected under 35 U.S.C. 103(a) as being unpatentable over Fischer et al. (US 5,747,568) in view of (a) EP0060421 (aka Endoh), (b) Rosenau et al. (US 5,821,302) and (c) Nishihara (US 5,900,446) or Margotte et al (US 4,204,047).

Fischer teaches a molding material comprising 30-80wt% of an elastomeric grafting base and 20-70wt% of a shell grafted onto the grafting base (abstract). The grafting base comprises 90-99.9% of at least one alkyl acrylate and 0.1-10wt% of a polyfunctional crosslinking monomer. The shell comprises 0-100% styrene or substituted styrenes, and 0-100% of an acrylonitrile or methyl methacrylate. The above-described particles are dispersed in a hard matrix comprising 60-90wt% styrene or substituted styrene and 10-40% acrylonitrile (col 1, lines 48-col2, line 16). The composition may further contain up to 30t% of additives such as fibers (Col 4, lines 26-34). This composition exhibit good weather resistance, aging resistance, and high impact strength (col 4, lines 46-53), and are usable as signs (col 4, line 48).

Fischer does not teach that a PMMA transparent layer or a protective topcoat may be applied to the taught composition. However, Endoh teaches an extrusion laminate comprising a polyvinylidene fluoride layer, and an adhesive layer comprising a methyl methacrylate polymer (abstract). The methyl methacrylate polymer may

Art Unit: 1794

comprise PMMA (page 9, lines 14+). The polyvinylidene fluoride layer provides the laminate with excellent weather resistance and chemical resistance. Thus, it would have been obvious to one of ordinary skill in the art to extrude the composition taught in Fischer with the polyvinylidene fluoride and PMMA layers taught in Endoh in order to improve the composition's weather and chemical resistance.

Fischer also does not teach that the composition may comprise a polycarbonate. However, Margotte and Nishihara each individually teaches a composition comprising a core/shell graft copolymer compounded with polycarbonate. Margotte teaches the addition of 20-80pbw polycarbonate to said mixture (abstract). The polycarbonate should have a molecular weight of 20,000-80,000 (col 4, lines 1+) and is granulated (col 6, lines 1+). Said mixture has the benefit of improved strength, dimensional stability, and processability (col 2, lines 1+). Nishihara teaches a composition comprising a core/shell polymer and 10-90pbw of polycarbonate (col 4, lines 30+) with a molecular weight of 10,000-100,000 (col 6, line 56). Said blend has a good combination of processability, impact resistance and rigidity (col 7, lines 45+). Thus, it would have been obvious to one of ordinary skill in the art at the time the invention was made to compound the core/shell graft copolymer taught in Fischer with 10-90pbw polycarbonate. The motivation for doing so would have been to improve the composition's processability, high impact resistance, and rigidity.

With respect to the "ground or granulated" limitation, the examiner takes the position said limitation is a method limitation. Specifically, the specification teaches that the polycarbonate is added in "granulated or ground" form (page 18-page 19) and then

mixed with the other components at 180-400°C (page 21, lines 26+). At those processing temperatures, the polycarbonate will melt and will not maintain its granulated or ground form (polycarbonate is herein understood to typically melt at 374-500°F). Thus, the method in which the polycarbonate is supplied to the composition is herein understood not to materially affect the final product. No showing has been made that the form in which the polycarbonate is supplied affects the final product.

Fischer does not teach the claimed particle size of the graft copolymer. However, Rosenau teaches the particle size of said particles may be selected based upon the desired glossiness/roughness of the resulting layer (col 3, lines 5+). Thus, it would have been obvious to the skilled artisan to optimize the particle size of the graft polymers taught in Fischer in order to optimize the desired gloss/dullness of the resulting film.

8. Claim 30 is rejected under 35 U.S.C. 103(a) as being unpatentable over (a) Fischer et al. (US 5,747,568) in view of WO96/09928 (aka Sallmetall), Rosenau, and Margotte or Nishihara, (b) Fischer et al. (US 5,747,568) in view of Ellison US 5,985,079), Rosenau, and Margotte or Nishihara, (c) Rosenau et al. (US 5,821,302) in view of Ellison (US 5,985,079) and Margotte, (d) Rosenau et al. (US 5,821,302) in view of Trabert et al. (US 5,318,737) and Margotte, (e) Rosenau et al. (US 5,821,302) in view of EP0060421 (aka Endoh) and Margotte, or (f) Fischer et al. (US 5,747,568) in view of EP0060421 (aka Endoh), Rosenau, and Margotte or Nishihara, as applied above, and further in view of Tsai et al. (US 5,858,550).

Fischer in view of Sallmetall, Fischer in view of Ellison, Rosenau in view of Trabert, Rosenau in view of Endoh, Fischer in view of Endoh, and Rosenau in view of Ellison are relied upon as above. However, none of the references teach that the ratio of MFI values of the individual components of the laminated sheet is not more than 3:1. However, Tsai teaches that the constituents used to form a coextruded sheet should have melt properties that are substantially similar to one another (col 7, lines 51+). Thus, it would have been obvious to one of ordinary skill in the art to utilize resins that have MFI values substantially similar to one another so that the films can be effectively coextruded.

9. Claims 26 is rejected under 35 U.S.C. 103(a) as being unpatentable over (a) Fischer et al. (US 5,747,568) in view of WO96/09928 (aka Sallmetall), Rosenau, and Margotte or Nishihara, (b) Fischer et al. (US 5,747,568) in view of Ellison US 5,985,079, Rosenau, and Margotte or Nishihara, (c) Rosenau et al. (US 5,821,302) in view of Ellison (US 5,985,079) and Margotte, (d) Rosenau et al. (US 5,821,302) in view of Trabert et al. (US 5,318,737) and Margotte, (e) Rosenau et al. (US 5,821,302) in view of EP0060421 (aka Endoh) and Margotte, or (f) Fischer et al. (US 5,747,568) in view of EP0060421 (aka Endoh), Rosenau, and Margotte or Nishihara, as applied above.

Fischer in view of Sallmetall, Fischer in view of Ellison, Rosenau in view of Trabert, Rosenau in view of Endoh, Fischer in view of Endoh, and Rosenau in view of Ellison are relied upon as above. None of the references teaches the desired thickness of the laminate. However, Rosenau and Fischer each teach rigid compositions with

enhanced impact resistance. Furthermore, Ellison, Trabert, Sallmetall, and Endoh each teach the application of protective layers to such substrates. Thus, it would have been obvious to one of ordinary skill in the art to vary the thickness of the laminate so that the laminate has the desired rigidity, impact resistance, and weather resistance for the intended end use. Furthermore, it would have been obvious to one of ordinary skill in the art to vary the thickness of the substrate composition in order to obtain the desired rigidity and impact resistance in the final product.

10. Claim 43 is rejected under 35 U.S.C. 103(a) as being unpatentable over Fischer et al. (US 5,747,568) in view of (a) Zabrocki et al (US 5,306,548) or McDonagh (US 4,169,180), (b) Rosenau, and (c) Nishihara (US 5,900,446) or Margotte et al (US 4,204,047).

Fischer teaches a molding material comprising 30-80wt% of an elastomeric grafting base and 20-70wt% of a shell grafted onto the grafting base (abstract). The grafting base comprises 90-99.9% of at least one alkyl acrylate and 0.1-10wt% of a polyfunctional crosslinking monomer. The shell comprises 0-100% styrene or substituted styrenes, and 0-100% of an acrylonitrile or methyl methacrylate. The above-described particles are dispersed in a hard matrix comprising 60-90wt% styrene or substituted styrene and 10-40% acrylonitrile (col 1, lines 48-col2, line 16). The composition may further contain up to 30t% of additives such as fibers (Col 4, lines 26-34). This composition exhibit good weather resistance, aging resistance, and high impact strength (col 4, lines 46-53), and are usable as signs (col 4, line 48).

Fischer does not teach that a styrene-acrylonitrile copolymer layer may be applied to the taught composition. However, Zabrocki teaches a weatherable film for lamination to an underlying substrate. The film comprises an outer layer of weather resistant polymer comprising styrene/acrylonitrile copolymer or butyl acrylate-reinforced styrene/acrylonitrile copolymer (abstract). The film can be utilized with high impact polystyrene substrates (see example 1). NOTE: the composition taught in Fischer is a HIPS composition. For a definition of a HIPS, Applicant's attention is directed to US 4,749,737 (see col 5, lines 27+). Thus, it would have been obvious to one of ordinary skill in the art to apply the styrene-acrylonitrile weatherable film taught in Zabrocki to the composition taught in Fischer in order to improve said composition's weather resistance.

Similarly, McDonagh teaches a protective layer comprising methacrylate/crosslinked styrene-acrylonitrile/uncrosslinked styrene-acrylonitrile (abstract). Said composition is applied to base layers that lack superior weather resistance (abstract). Thus, it would have been obvious to one of ordinary skill in the art to apply the protective layer taught in McDonagh to the composition taught in Fischer in order to improve its weather resistance.

Fischer also does not teach that the composition may comprise a polycarbonate. However, Margotte and Nishihara each individually teaches a composition comprising a core/shell graft copolymer compounded with polycarbonate. Margotte teaches the addition of 20-80pbw polycarbonate to said mixture (abstract). The polycarbonate should have a molecular weight of 20,000-80,000 (col 4, lines 1+) and is granulated (col

6, lines 1+). Said mixture has the benefit of improved strength, dimensional stability, and processability (col 2, lines 1+). Nishihara teaches a composition comprising a core/shell polymer and 10-90pbw of polycarbonate (col 4, lines 30+) with a molecular weight of 10,000-100,000 (col 6, line 56). Said blend has a good combination of processability, impact resistance and rigidity (col 7, lines 45+). Thus, it would have been obvious to one of ordinary skill in the art at the time the invention was made to compound the core/shell graft copolymer taught in Fischer with 10-90pbw polycarbonate. The motivation for doing so would have been to improve the composition's processability, high impact resistance, and rigidity.

Fischer does not teach the claimed particle size of the graft copolymer. However, Rosenau teaches the particle size of said particles may be selected based upon the desired glossiness/roughness of the resulting layer (col 3, lines 5+). Thus, it would have been obvious to the skilled artisan to optimize the particle size of the graft polymers taught in Fischer in order to optimize the desired gloss/dullness of the resulting film.

11. Claim 43 is rejected under 35 U.S.C. 103(a) as being unpatentable over Rosenau et al. (US 5,821,302) in view of (a) Zabrocki et al (US 5,306,548) or McDonagh (US 4,169,180) and (b) Margotte (US 4,204,047)

Rosenau teaches a thermoplastic molding composition comprising (a) 50-100wt% of a styrene compound, and (b) 0.1-70wt% of a graft polymer. The styrene compound may comprise 0-40wt% acrylonitrile. The graft polymer comprises 30-90wt% of a core, and 10-70wt% of a graft shell. The core comprises 50-99.99wt% of C1-10

Art Unit: 1794

alkyl acrylate, and 0.01-5wt% of a polyfunctional crosslinking monomer. The shell comprises 50-100wt% styrene and 0-40wt% acrylonitrile (col 1, lines 4-65). The graft polymer has an average particle diameter of less than 700nm. The composition may further comprise up to 70wt% of a particulate polymer and up to 70wt% of a polycarbonate blend (col 9, lines 59+). The composition is useful in extrusions, injection moldings, calendaring, and rolling (col 10, lines 58-64), and may be utilized to make automotive parts.

Rosenau does not teach that a styrene-acrylonitrile copolymer layer may be applied to the taught composition. However, Zabrocki teaches a weatherable film for lamination to an underlying substrate. The film comprises an outer layer of weather resistant polymer comprising styrene/acrylonitrile copolymer or butyl acrylate-reinforced styrene/acrylonitrile copolymer (abstract). The film can be utilized with high impact polystyrene substrates (see example 1). NOTE: the composition taught in Rosenau is a HIPS composition. For a definition of a HIPS, Applicant's attention is directed to US 4,749,737 (see col 5, lines 27+). Thus, it would have been obvious to one of ordinary skill in the art to apply the styrene-acrylonitrile weatherable film taught in Zabrocki to the composition taught in Rosenau in order to improve said composition's weather resistance.

Similarly, McDonagh teaches a protective layer comprising methacrylate/crosslinked styrene-acrylonitrile/uncrosslinked styrene-acrylonitrile (abstract). Said composition is applied to base layers that lack superior weather resistance (abstract). Thus, it would have been obvious to one of ordinary skill in the art

to apply the protective layer taught in McDonagh to the composition taught in Rosenau in order to improve its weather resistance.

Rosenau teaches the composition may comprise polycarbonate but does not teach the claimed molecular weight of said polycarbonate. However, Margotte teaches a composition comprising an impact resistance of a core/shell graft copolymer compounded with polycarbonate. Margotte teaches the addition of 20-80pbw polycarbonate to said mixture (abstract). The polycarbonate should have a molecular weight of 20,000-80,000 (col 4, lines 1+) and is granulated (col 6, lines 1+). Said mixture has the benefit of improved strength, dimensional stability, and processability (col 2, lines 1+). Thus, it would have been obvious to one of ordinary skill in the art at the time the invention was made to compound the core/shell graft copolymer taught in Rosenau with polycarbonate having a molecular weight o 20,000-80,000. The motivation for doing so would have been to improve the composition's processability, high impact resistance, and rigidity.

Response to Arguments

Applicant's arguments filed September 23, 2008 have been fully considered but they are not persuasive.

REGARDING REJECTION 1

Applicant argues Nishihara relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent.

Art Unit: 1794

Applicant argues since Nishihara does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

The examiner respectfully disagrees. It is noted Fischer, not Nishihara, is relied upon to teach the claimed core/shell graft copolymer. In response to applicant's arguments against the references individually, one cannot show nonobviousness by attacking references individually where the rejections are based on combinations of references. See *In re Keller*, 642 F.2d 413, 208 USPQ 871 (CCPA 1981); *In re Merck & Co.*, 800 F.2d 1091, 231 USPQ 375 (Fed. Cir. 1986).

To the extent applicant is arguing the core/shell graft copolymers of Fischer and Nishihara are not analogous because the graft core of Fischer comprises 0.1-10wt% crosslinking monomer, Applicant has failed to provide any evidence or argument to support said position. Furthermore, the examiner is not aware of any reason why 0.1-10wt% crosslinking monomer in the core would drastically alter the properties and chemistry of the core/shell graft copolymer as it relates to mixtures with polycarbonates.

REGARDING REJECTION #2

Applicant argues Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft

copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

The examiner respectfully disagrees. It is noted Fischer, not Margotte, is relied upon to teach the claimed core/shell graft copolymer. In response to applicant's arguments against the references individually, one cannot show nonobviousness by attacking references individually where the rejections are based on combinations of references. See *In re Keller*, 642 F.2d 413, 208 USPQ 871 (CCPA 1981); *In re Merck & Co.*, 800 F.2d 1091, 231 USPQ 375 (Fed. Cir. 1986).

To the extent applicant is arguing the core/shell graft copolymers of Fischer and Margotte are not analogous because the graft core of Fischer comprises 0.1-10wt% crosslinking monomer, Applicant has failed to provide any evidence or argument to support said position. Furthermore, the examiner is not aware of any reason why 0.1-10wt% crosslinking monomer in the core would drastically alter the properties and chemistry of the core/shell graft copolymer as it relates to mixtures with polycarbonates.

REGARDING REJECTION #3

Applicant argues, as discussed above, that Nishihara relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Nishihara does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents,

Art Unit: 1794

persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #4

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #5

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #6

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #7

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #8

Applicant argues, as discussed above, that Nishihara relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Nishihara does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #9

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #10

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #11

Applicant argues, as discussed above, that Nishihara relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Nishihara does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #12

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #13

Applicant argues, as discussed above, that Nishihara relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Nishihara does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #14

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #15

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #16

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #17

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #18

Applicant argues, as discussed above, that Nishihara relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Nishihara does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #19

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #20

Applicant argues, as discussed above, that Nishihara relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Nishihara does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #21

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #22

Applicant argues, as discussed above, that Nishihara relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Nishihara does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #23

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #24

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #25

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #26

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #27

Applicant argues, as discussed above, that Nishihara relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Nishihara does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #28

Applicant argues, as discussed above, that Nishihara relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Nishihara does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #29

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #30

Applicant argues, as discussed above, that Nishihara relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Nishihara does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #31

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #32

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

REGARDING REJECTION #33

Applicant argues, as discussed above, that Margotte relates to combining polycarbonate with a graft copolymer in which the graft base does not comprise any crosslinking agents. On the other hand, the present claims require a polycarbonate to be co-extruded with a graft copolymer wherein the graft base comprises at least 0.1% of crosslinking agent. Applicant argues since Margotte does not disclose combining polycarbonate with graft copolymer with a graft base comprising crosslinking agents, persons having ordinary skill in the art would not combine the cited references to arrive at the present invention.

Said argument is not persuasive for the reasons noted above.

Conclusion

THIS ACTION IS MADE FINAL. Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to KEVIN R. KRUEER whose telephone number is (571)272-1510. The examiner can normally be reached on Monday-Friday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Rena Dye can be reached on 571-272-3186. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 1794

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

/Kevin R Kruer/
Primary Examiner, Art Unit 1794